

CONTRACT MANUFACTURING EQUIPMENT

Kalyani Mobility Drivelines is a premier CV Joint & Driveshaft Design, Prototype, and Validation Center. Our products are used in applications around the globe. Our manufacturing machining centers and grinding equipment are available for contract manufacturing to meet your manufacturing needs. “Transmitting Torque Through Angle”

CNC MULTITASKING (Automated Load/Unload)

- 1 – Okuma, MULTUS B250II 23in. Dia. x 19.5in. x 31.5in. x 8in.
- 1 – Okuma, MULTUS B300II 24.5in. Dia. x 23in. x 37in. x 6.5in.



OKUMA, Multus, B300II

CNC VERTICAL MILLS

- | | |
|-------------------------------------|---------------------------|
| 1 – DMG Mori, 75 Mono Block, 5-Axis | 29.5in. x 25.5in. x 22in. |
| 1 – HURCO, VMX42ui, 5-xis | 42in. x 20.5in. x 20.5in. |
| 1 – HURCO, VMX30ui, 5-Axis | 30in. x 20in. x 20.5in. |
| 1 – Mazak, VTC-20B | 44in. x 20in. x 20in. |
| 1 – Mazak, VTC-200/50 | 44.5in. x 20in. x 23in. |
| 3 – Mazak, VTC-200 | 30in. x 30in. x 30in. |
| 1 – Mazak, VCN 530C | 30in. x 20in. x 20.5in. |
| 1 – HAAS, EC-500 | 32in. x 20in. x 28in. |

CNC LATHES

- | | |
|----------------------------|--------------------|
| 1 – Okuma, LB3000EXII C450 | 12in. Dia. x 20in. |
| 1 – Mazak, QT-350 | 24in. Dia. x 60in. |
| 1 – Mazak, QT-250HP | 17in. Dia. x 24in. |
| 1 – Mazak, QTN 250 II | 17in. Dia. x 20in. |
| 1 – Mazak, QT 30 | 17in. Dia. x 28in. |
| 1 – Mazak, QT25L | 17in. Dia. x 32in. |



DMG Mori 5-Axis

Application Policy

Capacity ratings, features, and specifications vary depending upon the model and type of service. Application approvals must be obtained from Kalyani Mobility Drivelines; contact our representative for application approval. We reserve the right to change or modify our product specifications, configurations, or dimensions at any time without notice.

Office

1015 W. Cedar St
Standish, Michigan 48658

Business Enquiry

John Shelton
Phone: (989) 846-1000
Email: Sales@kmdrivelines.com
Visit: www.kmdrivelines.com



I.D. GRINDING & HONING

- 1 – Heald, No. 72-A 15.5in. x 5.5in. Dia. x 10.25in. Stroke
- 1 – SUNNEN, Hone 6.5in. Dia.

O.D. GRINDING

- 1 – Browne & Sharpe, No. 3 12in. Dia. x 42in.
- 1 – Okamoto, OGM12-36U11 12in. Dia. X 36in.
- 1 – Shigiya, GPS-30 12in. Dia. x 30in.

SURFACE AND JIG GRINDING

- 1 – Surface: Okamoto, 12-24DX 12in. & 24in.
- 1 – Surface: Okamoto, 6.18
- 1 – Jig: Moore, N. 3 18in. max

INSPECTION

- 1 – Mitutoyo, CMM, SJ-410
- 1 – Mitutoyo, CMM, BH706 24.5in. Dia. x 23in. x 37in.
- 1 – Zeiss, CMM, Contura G2

OTHER

- 1 – Vibro Finishing Mill, Sweco, FM10
- 1 – Pull Broach, Colonial, HAS 25-72
- 3 – Manual Mills, Bridgeport
- 1 – Hydraulic Press, Dake, 5-075



Hurco VMX42Ui

A B

Application Policy

Capacity ratings, features, and specifications vary depending upon the model and type of service. Application approvals must be obtained from Kalyani Mobility Drivelines; contact our representative for application approval. We reserve the right to change or modify our product specifications, configurations, or dimensions at any time without notice.

© 2024 Kalyani Mobility Drivelines. All rights reserved.

Office

1015 W. Cedar St
Standish, Michigan 48658

Business Enquiry

John Shelton
Phone: (989) 846-1000
Email: Sales@kmdrivelines.com
Visit: www.kmdrivelines.com

KALYANI MOBILITY DRIVELINES

